

PANELES LED DRIVER EXTERNO

VIDA ÚTIL: 25.000 hs

EFICIENCIA: 85Lm/Watt

ÁNGULO: 120°

TENSIÓN DE ENTRADA: 180-240 VCa 50/60Hz

IP: 20

DRIVER: externo

Alto rendimiento lumínico,
línea de aluminio inyectado.



PREMIUM






PREMIUM



PREMIUM

código	5700	5702	5703	5705	5706	5708
potencia	6 w	6 w	12 w	12 w	18 w	18 w
flujo luminoso	510 lm	510 lm	1020 lm	1020 lm	1530 lm	1530 lm
temp. color	3000 K	6000 K	3000 K	6000 K	3000 K	6000 K
unidad por caja	10	10	10	10	10	10
ean 13	4 958400570004	4 958400570202	4 958400570301	4 958400570509	4 958400570608	4 958400570806



PREMIUM






PREMIUM



PREMIUM

código	5709	5711	5750	5752	5753	5755
potencia	24 w	24 w	6 w	6 w	12 w	12 w
flujo luminoso	2040 lm	2040 lm	510 lm	510 lm	1020 lm	1020 lm
temp. color	3000 K	6000 K	3000 K	6000 K	3000 K	6000 K
unidad por caja	10	10	10	10	10	10
ean 13	4 958400570905	4 958400571100	4 958400575009	4 958400575207	4 958400575306	4 958400575504



PREMIUM



PREMIUM

código	5756	5758	5759	5761
potencia	18 w	18 w	24 w	24 w
flujo luminoso	1530 lm	1530 lm	2040 lm	2040 lm
temp. color	3000 K	6000 K	3000 K	6000 K
unidad por caja	10	10	10	10
ean 13	4 958400575603	4 958400575801	4 958400575900	4 958400576105

